

Reply to Queries on ANPR

| S.No | As per RFP | Request | Reply |
|------|---|---|---|
| 1 | Storage: 2 internal SATA bays (supporting up to 20 TB per HDD) | Kindly Consider the Storage supporting Minimum 12 TB per HDD | We said upto 20 TB. It is covered. |
| 2 | External Storage Support: eSATA/NAS/SAN/ISCSI for long-term retention | External Storage support is not available as per requirement of NVR Cameras, we kindly request you to consider the Storage Support for NVR as External Storage as Support Smart IPC (with SD card) | As per RFP |
| 3 | RAID Support: RAID 5 (for data redundancy and faster recovery) | As per industry standards, 8-channel NVRs do not support RAID-5, since RAID-5 requires a minimum of three HDD slots, whereas most 8-channel NVR models support only 1 or 2 HDDs. Therefore, RAID-5 is technically not feasible for this category of NVR. | Agreed. Not needed. |
| 4 | Ingress Protection: Minimum IP50 or placed in IP65-rated enclosure for dusty mining environments. | AI Fusion Cameras come with IP ratings as they are intended for outdoor installation. However, NVRs are indoor devices and are typically installed inside cabinets or protective enclosures. | The cameras we have specified are weatherproof with an IP67 rating. The NVRs will be installed indoors (Security Room / Weighbridge Room / Office Room). If any location does not have a suitable |

| | | | |
|---|---|---|--|
| | | <p>In dusty mining environments, the NVR will be placed within an IP65-rated enclosure, ensuring adequate protection.</p> <p>We request you to kindly consider this arrangement as meeting the environmental protection criteria.</p> | <p>shelter, we will place the equipment in an IP65-rated weatherproof enclosure.</p> |
| 5 | <p>Considering the Pre-Bid Meeting was held and the need to incorporate clarifications into our proposal, we kindly request the authority to extend the bid submission deadline by at least one week or more from the current due date...</p> | | <p>01st December 2025.</p> |

Sd/-
Director of Mines and Geology(FAC)